

Description

Black rubber ball wheels with zinc-plated brackets.

Hub with plain bore hole which directly houses the axle.

Uses

Suitable for indoor applications, without aggressive chemicals. They can be used on fragile flooring, even carpet.

Examples of recommended applications: house and office furniture with low carrying capacity.

Environments of use

Suitable for domestic environments without aggressive chemicals.

WEAK ACIDS	
STRONG ACIDS	
WATER	
ALCOHOL	

WEAK BASES	
STRONG BASES	
HYDROCARBONS	
SOLVENTS	

For information on the compatibility of the component wheel materials with specific aggressive chemical substances, see table at page 36.

Floors


Suitable on tiles and delicate flooring; not recommended on abrasive, unpaved floors or in presence of processing residues.

Not recommended in presence of obstacles.





		2 pc package											
mm	kg	CODE	kg	CODE	mm	mm	mm	mm	daN				
30	0.11	334101	0.26	334001	48	40x40	27x27	5	10				
40	0.15	334102	0.34	334002	59	40x40	27x27	5	20				
50	0.23	334103	0.51	334003	69	47x47	35x35	6	30				



		2 pc package											
mm	kg	CODE	kg	CODE	mm	mm	mm	daN					
30	0.09	333101	0.21	333001	46	32	9	10					
40	0.13	333102	0.30	333002	57	32	9	20					
50	0.20	333103	0.43	333003	66	36	10	30					



		2 pc package											
mm	kg	CODE	kg	CODE	mm	mm	mm	mm	daN				
30	0.10	336101	0.25	336001	51	SPANNER 13	M8	15	10				
40	0.14	336102	0.33	336002	63	SPANNER 13	M8	15	20				
50	0.22	336103	0.47	336003	73	SPANNER 13	M8	15	30				