



GREY NON-MARKING THERMOPLASTIC RUBBER WHEELS WITH POLYPROPYLENE CENTRE



Description

Tyre: grey non-marking thermoplastic rubber.

Centre: polypropylene.

Hub with plain bore which houses the axle.

Uses

Suitable for institutional trolleys, especially for catering.

The grey non-marking thermoplastic rubber tyre makes them also suitable on delicate floorings.

They can resist frequent washings and are therefore a good option in those environments where cleanliness must be guaranteed.

Environments of use

Suitable for industrial and institutional environments, also in the presence of humidity. Not suitable in the presence of organic solvents, chlorinated substances, hydrocarbons and mineral oils. Not recommended in presence of strong organic and mineral acids.

WEAK ACIDS			
STRONG ACIDS			
WATER			
ALCOHOL			

WEAK BASES			
STRONG BASES			
HYDROCARBONS			
SOLVENTS			

For information on the compatibility of the component wheel materials with specific aggressive chemical substances, see table at page 36.

Floors

It does not stain or damage fragile floors. Suitable for tiles and cement-resin.


Not recommended on abrasive, unpaved floors or in the presence of processing residues.





																		
mm	mm	kg	COD.	mm	mm	daN												
40	18	0,01	381100	8	21	30												
50	20	0,02	381101	8	22	40												
60	24	0,04	381102	8	28	60												
75	24	0,05	381203	8	28	70												
80	24	0,07	381103	8	28	70												


Institutional brackets



- 1) Plate: electrolytically galvanised steel plate
 - 2) Fork: electrolytically galvanised steel plate
 - 3) Ball race ring: electrolytically galvanised steel plate
 - 4) Swivel actions: double ball ring with grease lubrication
 - 5) King pin: integrated with the plate and cold-riveted
- Available with front locking brakes


																		
mm	mm	kg	COD.	kg	COD.	kg	COD.	kg	COD.	mm	mm	mm	mm	mm	mm	daN		
40	18	0,09	384200	0,10	385200	0,12	388200			59	42x42	30x30	5	24	78	30		
50	18	0,13	384201	0,14	385201	0,15	388201			66	55x55	40x40	6	24	78	40		
60	24	0,22	384202	0,19	385202	0,26	388202			83	60x60	45x45	6	21	83	60		
75	24	0,26	384303	0,22	385303	0,32	388303			101	60x60	45x45	6	25	91	70		
80	24	0,28	384203	0,24	385203	0,33	388203			104	60x60	45x45	6	25	91	70		

Supporti per collettività



- 1) Plate: electrolytically galvanised steel plate
 - 2) Fork: electrolytically galvanised steel plate
 - 3) Ball race ring: electrolytically galvanised steel plate
 - 4) Swivel actions: double ball ring with grease lubrication
 - 5) King pin: integrated with the plate and cold-riveted
- Available with front locking brakes

																		
mm	mm	kg	COD.	kg	COD.	mm	mm	mm	mm	mm	mm	mm	mm	daN	3 km/h			
40	18	0,08	383200	0,11	387200	59	35	10	24	78	30							
50	18	0,10	383201	0,12	387201	66	35	10	24	78	40							
60	24	0,19	383202	0,22	387202	83	41	12	21	83	60							
75	24	0,23	383303	0,28	387303	101	41	12	25	91	70							
80	24	0,24	383203	0,29	387203	104	41	12	25	91	70							



- 1) Plate: electrolytically galvanised steel plate
 - 2) Fork: electrolytically galvanised steel plate
 - 3) Ball race ring: electrolytically galvanised steel plate
 - 4) Galvanised steel threaded stem
 - 5) Swivel actions: double ball ring with grease lubrication
- Available with front locking brakes

																		
mm	mm	kg	COD.	kg	COD.	mm	mm	mm	mm	mm	mm	mm	mm	daN	3 km/h			
40	18	0,09	386200	0,12	389200	59	35	M8	15	24	78	30						
50	18	0,11	386201	0,14	389201	66	35	M8	15	24	78	40						
60	24	0,22	386202	0,26	389202	83	41	M12	25	21	83	60						
75	24	0,26	386303	0,32	389303	101	41	M12	25	25	91	70						
80	24	0,28	386203	0,33	389203	104	41	M12	25	25	91	70						

Options available to order



Various dimensions
stems