


TRANSPARENT POLYURETHANE WHEELS WITH METHACRYLATE CENTRE



Description

Tyre: transparent polyurethane.

Centre: methacrylate.

Hub with plain bore hole which directly houses the axle.

Zinc-plated brackets.

Uses

Suitable for indoor applications, without aggressive chemicals. They can be used on delicate flooring, even carpet.

Examples of recommended applications: house and office furniture with low carrying capacity.

Environments of use

Suitable for domestic environments without aggressive chemicals.

WEAK ACIDS	
STRONG ACIDS	
WATER	
ALCOHOL	

WEAK BASES	
STRONG BASES	
HYDROCARBONS	
SOLVENTS	

For information on the compatibility of the component wheel materials with specific aggressive chemical substances, see table at page 36.













Floors

Suitable on tiles and fragile flooring; not recommended on abrasive, unpaved floors or in presence of processing residues.












Not recommended in presence of obstacles.





															
mm	mm	kg	CODE	mm	mm	mm	mm	mm	daN						
50	20	0.14	392002 	71	42x42	32x32	4.5	19	20						
75	22	0.33	392004 	103	60x60	43x43	6.5	28	40						



															
mm	mm	kg	CODE	mm	mm	mm	mm	daN							
50	20	0.14	392102 	71	M8	15	19	20							
75	22	0.31	392104 	103	M10	25	28	40							

Options available to order



Wheels
with thread
bracket
d. 78 mm



Wheels
with thread
bracket
d. 78 mm