



| S.R. NO. | COUPLING SIZE | NO.PER COUPL. | PART NO. | ØD1 | ØD2 | ØD3 | LB | A/F | A/C (MIN) | L1 | L2 | L3 | L4 | L | T | ØE1 | THREAD SIZE |
|----------|---------------|---------------|----------|------|------|-------|------|------|-----------|-----|------|------|----|-------|-----|-----|-------------|
| 1 | RB-105-3 | 3 | | | | | | | | | | | | | | | |
| 2 | RB-116-4 | 4 | RB/P-2 | 10.0 | 8.0 | 24 | 28 | 13.0 | 14.3 | 5.5 | 29.0 | 9.0 | 13 | 58.5 | 2.0 | 20 | MBx1.25P |
| 3 | RB-125-4 | 4 | | | | | | | | | | | | | | | |
| 4 | RB-144-6 | 6 | | | | | | | | | | | | | | | |
| 5 | RB-162-6 | 6 | | | | | | | | | | | | | | | |
| 6 | RB-178-6 | 6 | RB/P-3 | 12.0 | 10.0 | 30 | 34.5 | 17.0 | 18.8 | 7 | 36.5 | 13.0 | 15 | 72.5 | 2.0 | 22 | M10x1.5P |
| 7 | RB-198-10 | 10 | | | | | | | | | | | | | | | |
| 8 | RB-228-11 | 11 | RB/P-4 | 16.0 | 14.0 | 38 | 42 | 22.0 | 24.3 | 9 | 43.0 | 18.0 | 18 | 90.5 | 2.5 | 28 | M14x2P |
| 9 | RB-252-12 | 12 | | | | | | | | | | | | | | | |
| 10 | RB-285-11 | 11 | RB/P-5 | 19.9 | 16.0 | 47.5 | 51.5 | 24.0 | 26.3 | 10 | 52.5 | 24.0 | 20 | 109.5 | 3.0 | 34 | M16x2P |
| 11 | RB-320-12 | 12 | | | | | | | | | | | | | | | |
| 12 | RB-360-11 | 11 | RB/P-6 | 24.9 | 20 | 59 | 65.5 | 30.0 | 33.2 | 13 | 66.5 | 30.0 | 24 | 137.5 | 4.0 | 44 | M20x2.5P |
| 13 | RB-400-10 | 10 | | | | | | | | | | | | | | | |
| 14 | RB-450-12 | 12 | RB/P-7 | 29.9 | 25 | 74.5 | 58 | 30.0 | 33.2 | 13 | 58.5 | 44 | 30 | 149.5 | 4.0 | 56 | M20x2.5P |
| 15 | RB-500-14 | 14 | | | | | | | | | | | | | | | |
| 16 | RB-560-10 | 10 | RB/P-8 | 50 | 48 | 109 | 79 | 55.0 | 61.2 | 23 | 80 | 59 | 50 | 220 | 8.0 | 90 | M36x4P |
| 17 | RB-630-12 | 12 | | | | | | | | | | | | | | | |
| 18 | RB-710-12 | 12 | RB/P-9 | 60 | 58 | 137.5 | 94 | 65.0 | 72.5 | 26 | 95 | 73 | 55 | 259 | 10 | 110 | M42x4.5P |
| 19 | RB-800-14 | 14 | | | | | | | | | | | | | | | |
| 20 | RB-900-16 | 16 | | | | | | | | | | | | | | | |
| 21 | RB-1000-18 | 18 | | | | | | | | | | | | | | | |

NOTES:-
 1. # SR.NO. 3-PLAIN WASHER IS SEPARATE PART IN RB/P-8 & RB/P-9.
 2.SURFACE COATING- ZINC ELECTROPLATING. (YELLOW)

| REV. | DMRN NO. | DESCRIPTION | REV. BY | APPD. BY | DATE |
|------|----------|-------------|---------|----------|------|
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

| TITLE: | CUSTOMER NAME: | SR.NO. | DESCRIPTION | MATERIAL | QTY. |
|--------------------------------------|---------------------------|--------|--------------|-------------------|------|
| RB CPLG. PIN,BUSH & NYLOCK NUT ASSY. | GLOBAL POWER TRANSMISSION | 4 | NYLOCK NUT | STD | 1 |
| | | 3 | PLAIN WASHER | STD | 1 |
| | | 2 | BUSH | NATURAL RUBBER | 1 |
| | | 1 | PIN | EN 8/EN-80 BS 970 | 1 |

RATHI RATHI TRANSPOWER PVT LTD PUNE 411006

DRG. No.: R/M-4507/0

SCALE: NTS REF. No.: R/M-2660

APPROVED: SKT-467

AUTHORITY INITIALS SIGN DATE

DRAWN: SPK 18/02/15

CHECKED: RDB 18/02/15

APPROVED: SAS 18/02/15